

SLine108

Mode		FR (fullrange)		XO (crossover)	
Crossover High-Pass (Lo-Cut)	Frequency	60 Hz		90 Hz	
	Slope	18 dB/oct		18 dB/oct	
	Shape	Bessel		Bessel	
Crossover Low-Pass (Hi-Cut)	Frequency	20.000 Hz		20.000 Hz	
	Slope	12 dB/oct		12 dB/oct	
	Shape	Butterworth		Butterworth	
PEQ1	Frequency	317 Hz		317 Hz	
	Gain	-6,1 dB		-6,1 dB	
	Q	5,3		5,3	
	= Bandwidth	0,27 oct		0,27 oct	
PEQ2	Frequency	641 Hz		641 Hz	
	Gain	-4,9 dB		-4,9 dB	
	Q	3		3	
	= Bandwidth	0,45 oct		0,45 oct	
PEQ3	Frequency	2810 Hz		2810 Hz	
	Gain	-1,9 dB		-1,9 dB	
	Q	5,5		5,5	
	= Bandwidth	0,26 oct		0,26 oct	
PEQ4	Frequency	8697 Hz		8697 Hz	
	Gain	-1,9 dB		-1,9 dB	
	Q	5		5	
	= Bandwidth	0,28 oct		0,28 oct	
PEQ5 Hi--Shf	Frequency	10499 Hz		10499 Hz	
	Slope	12 dB/oct		12 dB/oct	
	Gain	+3,3 dB		+3,3 dB	
Limiter	Z(nom)	8 Ohm		8 Ohm	
	P(rms)	150 Watt		150 Watt	
	U(rms)	34,6 Volt		34,6 Volt	